
TIGER Neo III

JinKO Solar

54QL6-DV

525-545 Watt

MONO-FACIAL MODULE
WITH DUAL GLASS




Higher Power on Front Side

Leading power class based on the enhanced N-type TOPCon platform, achieved through cutting-edge technology and an optimized layout that captures more sunlight.

Optimized Heat resistance

Optimized temperature coefficient achieved via advanced graphical patterning, busbar and multi-cell technology.



Proven Low Light Performance

Enhanced cell structure ensures superior module performance under low-light conditions.

Industry Leading Warranty

Advanced metallization and iterated module encapsulation deliver superior resistance to PID, LID / LeTID, and UV degradation.

15Year Product Warranty | **30**Year Linear Power Warranty | **1**% First-year Degradation | **0.35**% Annual Degradation Over 30 Years

Mechanical Load Enhanced

Certified to withstand:
5400 Pa front side max static test load
2400 Pa rear side max static test load

- IEC61215:2021 / IEC61730:2023
- IEC61701 / IEC62716 / IEC60068 / IEC62804
- ISO9001:2015: Quality Management System
- ISO14001:2015: Environment Management System
- ISO45001:2018: Occupational health and safety management systems

TUV SUD · CE · PV CYCLE · CLEAN ENERGY COUNCIL MEMBER · POSITIVE QUALITY™ Continuous Quality Assurance

54QL6-DV 525-545 Watt

Mechanical Characteristics

Cell Type	N- type Mono-crystalline
No. of cells	216 (54×4)
Dimensions	1980×1134×30 mm
Weight	27.5 kg
Front Glass	2.0 mm, Anti-reflection Coating
Back Glass	2.0 mm, Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Protection Class	Class II
IEC Fire Type	Class C
Connector Type	JK03M/JK03M2/Others*
Output Cables (Including Connector)	⩾4.0 mm² (+): 500 mm , (-): 400 mm or Customized Length

* MC4-EVO2 available upon request and subject to availability

Packaging Configuration

Pallet Dimensions	1996×1110×1249 mm
Packing Detail (Two pallets = One stack)	36 pcs/pallets, 72 pcs/stack, 864 pcs/ 40'HQ Container

Specifications (STC)

Maximum Power - Pmax [Wp]*	525	530	535	540	545
Maximum Power Voltage - Vmp [V]	33.98	34.16	34.34	34.52	34.70
Maximum Power Current - Imp [A]	15.45	15.52	15.58	15.64	15.71
Open-circuit Voltage - Voc [V]	39.78	39.95	40.12	40.29	40.46
Short-circuit Current - Isc [A]	16.24	16.28	16.33	16.37	16.42
Module Efficiency STC [%]	23.38	23.60	23.83	24.05	24.27
Power Sorting	0 ~ + 3 %				
Temperature Coefficient of Pmax	-0.26 %/°C				
Temperature Coefficient of Voc	-0.24 %/°C				
Temperature Coefficient of Isc	0.046 %/°C				


STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5. *Power measurement tolerance: ±3%.

Application Conditions

Level T_{98} ⩽ 70 °C	- 40 °C to + 70 °C*
Maximum System Voltage	1500 V DC (IEC)
Maximum Series Fuse Rating	30 A

*Short-term up to 85°C; higher operation requires IEC TS 63126 testing


Engineering Drawings



*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

Electrical Performance

Power-Voltage Curves (54QL6-DV 535W)



Current-Voltage Curves (54QL6-DV 535 W)

